

Architectural Cable



Our architectural cable uses only the best stainless steel alloys to ensure your project shines for years to come. Product are available in both 302 / 304 and type 316 grades. We recommend using the 7x7 or 1x19 Stainless Steel cables for your next Architectural cable project. Other constructions and alloys are available by request.

1x19 Preformed T302/04 Stainless Steel Strand Non-Flexible

Diameter (inches)	Diameter (metric)	Construction	Min. Break Strength (lbs.)	Approx. Mass Wt(lbs.)/1000 ft
3/64	1.20	1x19	375	5.5
1/16	1.60	1x19	500	8.5
5/64	2.00	1x19	800	14
3/32	2.40	1x19	1,200	20
7/64	2.80	1x19	1,600	27
1/8	3.20	1x19	2,100	35
5/32	4.00	1x19	3,300	55
3/16	4.80	1x19	4,700	77
7/32	5.60	1x19	6,300	102
1/4	6.40	1x19	8,200	135

7x7 Preformed T302/04 Stainless Wire Rope Flexible

Diameter (inches)	Diameter (metric)	Construction	Min. Break Strength (lbs.)	Approx. Mass Wt(lbs.)/1000 ft
1/32	0.80	7x7	115	1.6
3/64	1.20	7x7	270	4.2
1/16	1.60	7x7	480	7.5
5/64	2.00	7x7	650	11
3/32	2.40	7x7	920	16
1/8	3.20	7x7	1,700	28
5/32	4.00	7x7	2,400	43
3/16	4.80	7x7	3,700	62
7/32	5.60	7x7	4,800	83
1/4	6.40	7x7	6,100	106
5/16	7.90	7x7	9,000	167
3/8	9.50	7x7	12,000	236

Strand Core

5881 Commerce Rd. Milton, FL 32583

Phone: 800-983-9926 - Email: sales@strandcore.com

strandcore.com